

TELAIO FORCELLA	Fox 36 Performance Elite, 29", 44mm offset, Grip 2 damper, S1: 150mm, S2-S6:160mm
COLLARINO	Alloy, 38.6mm
TELAIO	All new Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
SOSPENSIONI AMMORTIZZATORE	S2-S6: Fox Float X Performance elite series, 210x55mm, S1: Fox Float DPS Performance elite series, , 210x50mm
COCKPIT ATTACCO	Alloy Trail Stem, 35mm bar bore
SELLA	Bridge Comp, Hollow Cr-mo rails, 155/143mm
REGGISELLA	OneUp, Dropper Post-V2, MMX lever, 34.9 (S1:120mm, S2/S3:150mm, S4: 180mm, S5/S6: 210mm)
MANUBRIO	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 800mm, 35mm clamp
COCKPIT MANOPOLE	Deity Grips
REGGISELLA	SEAT POST, ONE UP, DROPPER, 2-BOLT,34.9, 120/150/180/210 TRAVEL, OFFSET 0MM,345/405/465/525MM, W/UFT REMOTE
FRENI FRENO ANT.	SRAM Code Silver Stealth, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	SRAM Code Silver Stealth, 4-piston caliper, hydraulic disc, 200mm
TRASMISSIONE INGRANAGGI	New SL 1.2 spider, 104BCD w/SRAM 32t Transmission compatible alloy ring
GUARNITURA	SRAM Alloy Crankset, Dub interface

COMANDI	SRAM AXS POD Controller
CAMBIO POST.	SRAM GX Eagle Transmission Derailleur
CATENA	SRAM GX Eagle Transmission Flattop Chain
CASSETTA	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
E-BIKE CABLAGGIO	Custom Specialized wiring harness
CARICATORE	Custom charger, 48V System w/ SL system charger plug
BATTERIA	Specialized SL1-320, fully integrated, 320Wh
ELETTRONICA MOTORE	New Specialized 1.2 SL Custom Rx Trail Tuned Motor
UI/REMOTE	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
ACCESSORI SWAT	SWAT CC steerer tube integrated tool with chain tool and link
PEDALI	PEDAL, TEST RIDE PEDALS PROVIDED BY SPECIALIZED
RUOTE PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5 x 2.3"
CAMERE	Standard, Presta Valve
RUOTA POST.	Traverse 27.5
RUOTA ANT.	Traverse 29
DINAMO	18.25kg (40 lb, 3.7 oz)