

Specifiche

TELAIO

Specialized M5 premium alloy, 150mm travel, 29" wheel front, 27.5" rear, BB height adjust, S-Sizing, internal cable routing, 148mm spacing

COLLARINO

Alloy, 38.6mm

FORCELLA

RockShox 35 Silver, 35mm stanchion, Turnkey damper, S1: 150mm travel, S2-S6: 160mm travel

SOSPENSIONI

AMMORTIZZATORE

RockShox Deluxe Select R, rebound adjust, S1: 52.5x210mm, S2-S6: 55x210mm

COCKPIT

ATTACCO

Alloy Trail Stem, 35mm bar bore

SELLA

Body Geometry Bridge Saddle, steel rails

NASTRO

Specialized Trail Grips

MANUBRIO

Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width

REGGISELLA

TranzX dropper, 34.9mm, S1: 100mm, S2: 125mm, S3: 150mm. S4-S5: 170mm, S6-200mm

FRENI

FRENO POST.

SRAM Guide RE, 200mm

FRENO ANT.

SRAM Guide RE, S1-S3: 200mm, S4-S6: 220mm

TRASMISSIONE

GUARNITURA

Praxis Forged/Custom Offset/ISIS Spindle Interface, 160mm

CATENA

SRAM NX Eagle, 12-speed

CASSETTA

SRAM NX Eagle, 12-speed, 11-50t

COMANDI

SRAM SX Eagle, 12-speed

CAMBIO POST.

SRAM SX Eagle, 12-speed

INGRANAGGI

SRAM X-Sync Eagle, 104 BCD, 34t, steel

RUOTE

MOZZO POST.

Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h

PNEUMATICO ANT.

Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"

RAGGI

DT Swiss Industry

PNEUMATICO POST.

Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"

CERCHI

Specialized 29, hookless alloy, 30mm inner width, tubeless ready

MOZZO ANT.

Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h

CAMERE

Standard, Presta Valve

E-BIKE

CABLAGGIO

Custom Specialized wiring harness

CARICATORE

Custom charger, 42V4A w/ Rosenberger plug, 100-240V

BATTERIA

Specialized M3-700, Integrated battery, 700Wh

ELETTRONICA

MOTORE

Specialized 2.2 Custom Rx Trail Tuned Motor

UI/REMOTE

Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote